

# Drivers

24 V

## Häfele Loox5 driver constant voltage 24 V



- > Version: With overload protection
- > Colour: Black
- > Degree of protection: IP20
- > Input voltage: 100–240 V~; 50–60 Hz
- > Output voltage: DC 24 V
- > Number of connections: 1x socket Loox5 24 V
- > Life time: >50,000 hours
- > Supplied with: 1 driver with mounting accessories

5 <sup>24 V</sup>	Output power	Output current	Standby power consumption	Dim. (L x W x H)	Cat. No.
	W	A	W	mm	
1	20	0.83	≤0,2 W	140 x 50 x 16	<b>833.95.008</b>
2	40	1.67	≤0.3 W	191 x 60 x 16	<b>833.95.010</b>
3	90	3.75	≤0.3 W	316 x 70 x 16	<b>833.95.011</b>

! Ambient temperature –25 °C to +45 °C  
Ensure that there is a sufficient air supply and circulation at the mounting location.

! Maximum lead length from the Loox5 driver to the device is 10 m. Long cable lengths in combination with large loads (strip light lengths) can result in voltage losses in the cable. These lead to visible loss of brightness in the lights. The illuminance listed with the lights has been determined with the rated output voltage of the driver. (12 V or 24 V).

### Country-specific main leads – 2 metre lead length, socket at the cable: C7

Plug design										
Description	UK	AU	EU	US	JP	CN	KR	TW	EU	US
Supplied with	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece
<b>Cat. No.</b>	<b>833.89.000</b>	<b>833.89.001</b>	<b>833.89.002</b>	<b>833.89.003</b>	<b>833.89.016</b>	<b>833.89.005</b>	<b>833.89.006</b>	<b>833.89.007</b>	<b>833.89.009</b>	<b>833.89.050</b>