

# Profile for surface mounting Häfele Loox, Profile 2190



12/24 V



> Material:
> Internal width:

> Diffuser width:> Installation:

Profile: Aluminium, Diffuser: Plastic 16 mm 18 mm For screw fixing with mounting clip, For surface mounting

#### Note

For LED strip lights up to a width of 10 mm. Permanent operation (≥8 hours/day) only with LED strip lights up to 9.6 W/ m. Distance of retaining clips max. 500 mm. The surface on the aluminium profile that is to be bonded must be cleaned before bonding to the LED strip lights. It must be completely clean, grease-free and dust-free! LED points are always visible when this profile is used. For homogeneous light without points, please use a COB strip.

## Supplied with

1 profile, 1 diffuser

Colour/finish	2500 mm
Profile: Silver coloured, Anodized, Diffuser: Opal white	833.72.981

Packing: 1 Piece

Order reference Please order retaining clip (optional) separately

### ightarrow Mounting clip for Häfele Loox profile for under mounting, profile 2190, 2191, 2192



Retaining clip 40°



Retaining clip 90°

> Material:	Stainless steel
> Colour/finish:	Silver coloured
> Length:	22 mm
> Suitable for:	Häfele Loox profile for under
	mounting, profile 2190, 2191, 2192
> Installation:	For screwing

#### Note

Minimum distance of retaining clips 500 mm

### Supplied with

1 pair of retaining clips with fixing material

Product type	Angle °	Cat. No.	
Mounting clip	40	833.74.833	
	90	833.74.832	
Packing: 1, 10 or 100 Pair			

# End cap, for Häfele Loox profile for under mounting, profile 2190

<ul><li>Material:</li><li>Equipment:</li><li>Suitable for:</li></ul>	Plastic With cable outlet Häfele Loox profile for under mounting, profile 2190			
<b>Supplied with</b> 1 pairs of end caps				
Colour/finish		Cat. No.		
Silver coloured		833.72.852		
Packing: 1, 10 or 100 Pair				

23.11.2021 ID 5763

мв 2.100

Häfele Loox replacement diffuserHäfele Loox5 aluminium profile switch

▶ MB 2.127

► MB 2.275