

BARdolino aluminium profile DUO

- high quality wall profile made of aluminum, anodised
- ideal for indirect lighting via wall reflection
- with horizontal mounting optionally upward and/or downward
- with vertical mounting optionally to the left and/or to the right
- with integrated cable guide
- suitable for LED strips of the LEDlight flex series
- RAL powder coating on request



Please refer to the notes on expansion and assembly at the end of the data sheet!

ALUMINIUM PROFILE

	62393141	62393142	62393143	62393145
Length	1000 mm	2010 mm	3020 mm	5030 mm
Width	51 mm			
Height	18,6 mm			
Material	Aluminium EN AW 6060			
Finish	anodised			
Weight	555 gr	1115 gr	1676 gr	2792 gr

COVER

	62399301	62399371	62399401
Description	cover opal white, for a homogenous and glare-free light distribution	cover satined, PMMA, for a diffused light distribution and concealment of the technology	cover clear, PMMA, for maximum light yield and protection of the LED strip
Material	PMMA		
Transmission in %	69	85	92
Fire protection class	B2 DIN4102		
Length	1000 mm		
Width	14,8 mm		
Height	8 mm		
	62379301	62379601	
Description	cover satined, PMMA, 30° lens for a directed light focus	cover satined, PMMA, 60° lens for a directed light focus	
Material	PMMA		
Transmission in %	85		
Fire protection class	B2 DIN4102		
Length	1000 mm		
Width	14,8 mm		
Height	8 mm		
	follow-up article to 6239934x		

For other lengths please replace the last digit of the article number by: 2 = 2.01m / 3 = 3.02m / 5 = 5.03m



END CAP

	62399669
Description	end cap set 2 pieces incl. 4 screws
Material	Aluminium EN AW 5052
Length	2 mm
Width	51 mm
Height	18,6 mm

Note: The screws for the end caps must be placed and screwed in at a right angle (90°) to the screw channel and may only be screwed in with a max. tightening torque of 0.35 Nm to prevent the screw head from unscrewing or the screw from overtightening (recommended bit PH1).



ACCESSORIES

	62393147	62399934
Description	profile connector incl. 4 screws M4	2x brackets 5cm, incl. screws and dowels, suitable for profiles of the BARdolino family



All aluminium profiles and covers are subject to certain length tolerances. This is +20/-0 mm irrespective of the length, i.e. a profile has at least the specified length, but can be up to 20 mm longer.

If you require an exact length, please specify this when ordering (article number 62397000).

Please note that the materials aluminum and PMMA can expand when the temperature changes vary greatly. With a temperature change of 20°C the expansion difference can be up to 1.2 mm per meter! This is no deficiency of the product but a normal physical process.

Installation note: If you directly install two aluminum profiles edge to edge (without end caps), please pay attention during installation, that you don't glue the LED strip directly over the joint, since the profiles at temperature fluctuations - especially at large lengths - will expand/contract (s. section 1) and then the LED tape may be damaged. At joints the LED strip has to be cut at the marked positions and reconnected with flexible solder bridges with corresponding expansion reserve (min. 5mm).

Intended Use

Profile:

- The LED profiles are a component for the reception of LED strips approved for this purpose. In combination with optional accessories such as covers, end caps, inserts, etc., LED luminaires can be produced which are used exclusively for general lighting or accent lighting and therefore do not serve emergency or safety lighting in particular.
- The assembly is carried out via appropriate holders or suspensions, which are offered as accessories. For brackets we recommend 3 brackets per running meter. The profiles are designed for mounting on a stable and straight surface. Depending on the substrate and local conditions, a higher number of brackets may be required and/or the installation material supplied (screws/plugs) must be replaced with suitable mounting material. The brackets must not be bent during assembly, as this has an influence on the holding force. It may not be possible to use the holders provided. Alternatively, the profile can be screwed directly to the substrate. In any case, the installer must ensure that the system is held securely.
- Make sure that the profile expands due to thermal influences. Sufficient space must be kept available for this purpose..
- The mounting instructions for the LED strips and power supplies must be viewed separately.
- The profile is to be used exclusively for the above shown installation situations.

Covers:

- All plastic covers made of PMMA have first-class photometric properties, but are very brittle due to the material, which means that the cover can splinter when subjected to mechanical influences (bending, sawing, other processing). There is a risk of injury, wear safety glasses and gloves! Plastic covers made of PC are not affected.
- PMMA or PC have a higher coefficient of thermal expansion than aluminium. This means that light slits may appear at the joints and terminations of the plastic covers, especially when the unit is not yet at operating temperature..
- To ensure that the cover is held securely, it must be clipped into the holding groove provided for this purpose along its entire length. In any case, the installer must ensure that the system is held securely.
- Alcoholic detergents remove plasticizers from the plastic profiles, which means that they lose their flexibility and can form cracks even when installed. We recommend cleaning only with a damp (clear water), soft cloth.

Accessories (end caps, holders, etc.):

- An LED profile and its accessories are not toys - these components may only be operated by persons who can assess the risks involved in handling them. There is a danger of swallowing small parts.

NOTE

Press marks or slight scratches on profiles are production-related and do not constitute a defect.

The guarantee period for the product is 5 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.